



| Job Name: | Contractor: |
|---------------|------------------------|
| Job Location: | P.O. Number: |
| Engineer: | Representative: |
| Tag: | Wholesale Distributor: |


DESCRIPTION

The Apollo Air Gap Drain (AGD4A6) is designed to funnel minor discharges from a Reduced Pressure Backflow Preventer's relief valve due to line pressure fluctuations and/or minor check valve fouling into the drainage system. Drain piping is easily attached to the AGD's threaded bottom outlet. The AGD4A6 fits Apollo's Model RP4A and RP4AN in sizes 2 ½", 3", 4", and 6". The AGD4A6 is ABS and PVC plastic with stainless steel screws and nuts.

Note: The AGD4A6 is **NOT** designed to collect the full discharge capacity of the relief valve. Please refer to page 4 for RP Relief Valve full discharge rates.







Shown without shut-off valves for clarity.

| RP4A Series RP4AN Series | AGD Model No. | Order Code | Α | В | С | D | Outlet Connection | Wt. Each |
|-----------------------------|---------------|------------|-------|-------|------|------|-------------------|----------|
| 2-1/2" | AGD4A6 | AGD4A6 | 11.28 | 10.87 | 2.63 | 3.13 | 2" FNPT | 0.7 |
| 3" | AGD4A6 | AGD4A6 | 11.28 | 10.87 | 2.63 | 3.13 | 2" FNPT | 0.7 |
| 4" | AGD4A6 | AGD4A6 | 12.02 | 10.51 | 2.63 | 3.13 | 2" FNPT | 0.7 |
| 6" | AGD4A6 | AGD4A6 | 13.32 | 11.76 | 2.63 | 3.13 | 2" FNPT | 0.7 |

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA ; www.apollovalves.com ; 704-841-6000

This specification is provided for reference only. Conbraco reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. SS1176 ©7/12 Page 1 of 4

DESCRIPTION


The Apollo Air Gap Drain (AGD4A8) is designed to funnel minor relief valve (RV) discharges due to line pressure fluctuations and/or minor check valve fouling into the drainage system. The AGD4A8 fits Apollo's Model RP4A and RP4AN in size 8".


Notes:

Drainage piping is easily attached to the threaded portion of the AGD. The female NPT size is listed in the table under "Outlet Connection". The AGD4A8 is ABS plastic with stainless steel screws and nuts. Drainage piping may be attached with a coupling and the appropriate cement or with a flexible pipe coupling. The OD is listed in the table under "OD of C".

The AGD4A8 is **NOT** designed to collect the full discharge capacity of the relief valve. Please refer to page 4 for RP Relief Valve full discharge rates.







| Model | AGD Model No. | Order Code | Α | В | OD of C | Outlet Connection | Wt. Each |
|-------|---------------|------------|------|-----|---------|--------------------------|----------|
| RP4A | AGD4A8 | AGD4A8 | 21.3 | 9.1 | 3" Pipe | 2-1/2" FNPT | 1.5 |
| RP4AN | AGD4A8 | AGD4A8 | 19.8 | 9.1 | 3" Pipe | 2-1/2" FNPT | 1.5 |

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA ; www.apollovalves.com ; 704-841-6000

This specification is provided for reference only. Conbraco reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. SS1176 ©7/12 Page 2 of 4


DESCRIPTION

The Apollo Air Gap Drain (AGD4A12IN) is designed to funnel minor relief valve (RV) discharges due to line pressure fluctuations and/or minor check valve fouling into the drainage system. The AGD4A12IN fits Apollo's Model RP4A and RP4AN in sizes 10" and 12".


Notes:

Drainage piping is easily attached to the threaded portion of the AGD. The female NPT size is listed in the table under "Outlet Connection". The AGD4A12IN is epoxy-coated steel with stainless steel screws.

The AGD4A12IN is **NOT** designed to collect the full discharge capacity of the relief valve. Please refer to page 4 for RP Relief Valve full discharge rates.








| Model | AGD Model No. | Order Code | Α | в | OD of C | Outlet Connection | Wt. Each |
|-------|---------------|------------|------|-----|---------|--------------------------|----------|
| RP4A | AGD4A12 | AGD4A12 | 26.3 | 7.7 | 4.00" | 3" FNPT | 4 |
| RP4AN | AGD4A12 | AGD4A12 | 23.4 | 7.7 | 4.00" | 3" FNPT | 4 |

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA ; www.apollovalves.com ; 704-841-6000

This specification is provided for reference only. Conbraco reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. SS1176 ©7/12 Page 3 of 4



Relief Valve Discharge Rates Model RP4A & RP4AN

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA ; www.apollovalves.com ; 704-841-6000